

480AA Series

Push Panels



SDC's push panels combined with SDC's operator, bollards and locking devices allow for complete access and egress solutions for ADA compliant applications. The contoured profile of SDC's Push Panels allows for activation from any approach and height level. Pressing any part of the touch panel columns will activate the device creating seamless operation for users in ADA applications.

Designed specifically for handicap access, automatic door activation and request-to-exit applications. Pressing any part of plate causes switch activation.

MODELS

482AA Push Panel Actuator, SPDT

484AA Push Panel Actuator, DPDT

STANDARD FEATURES

- Entire panel surface activates switch
- Naturally directs movement toward central activation column
- Sleek architectural profile
- No square edges to snag
- Wide sloping sides deflect impact from wheeled carts and conveyances
- Impact and vandal resistant design inhibits prying and tampering
- Wireless or hardwired
- Weather resistant



APPLICATIONS

- Surface wall or bollard mount
- Access control request-to-exit (REX)
- Automatic door activation



All can be used with wireless transmitter and receiver. See related products.



SPECIFICATIONS

	482AA36	484AA36
Panel	1/8" Aluminum	1/8" Aluminum
Dimensions	36" x 6"	36" x 6"
Sign	♿ PUSH TO OPEN	♿ PUSH TO OPEN
Sign Infill	Blue	Blue
Weight	7 lbs	7 lbs
Contact	SPDT	DPDT
Rating	15 Amp @ 125/250 VAC Resistive	15 Amp @ 125/250 VAC Resistive
Type	Momentary (MO)	Momentary (MO)
Depth	1 1/2"	1 1/2"
Operating Environment	-40°F to +221°F	-40°F to +221°F

CERTIFICATIONS

UL1054 Safety Special-Use Switches
CSA Listed

HOW TO ORDER

FOLLOW STEPS FOR ORDERING

Designates optional step

<p>1 SPECIFY MODEL</p> <p>482 Push Actuator, SPDT</p> <p>484 Push Actuator, DPDT</p> <p>2 SPECIFY SIGN</p> <p>A ♿ PUSH TO OPEN</p>	<p>3 SPECIFY SIZE</p> <p>A36 Panel, 36" x 6"</p> <p>4 SPECIFY FINISH</p> <p>V 628 Dull Aluminum </p>										
<table border="1" style="margin: auto;"> <thead> <tr> <th>STEP NUMBER:</th> <th>1</th> <th>2</th> <th>3</th> <th>4</th> </tr> </thead> <tbody> <tr> <td>ORDERING EXAMPLE:</td> <td>482</td> <td>A</td> <td>A36</td> <td>V</td> </tr> </tbody> </table>		STEP NUMBER:	1	2	3	4	ORDERING EXAMPLE:	482	A	A36	V
STEP NUMBER:	1	2	3	4							
ORDERING EXAMPLE:	482	A	A36	V							

RELATED PRODUCTS

WIRELESS TRANSMITTERS & RECEIVERS

400RC433 433MHz One Channel Receiver

400W1-433 433MHz Micro Transmitter

