

**SPACESAVER® MORTISE BOLT LOCKS FIT 1-3/4" FRAMES**

**AK LIST**




Dimensions: 8"L x 1-1/2"W x 1-5/8"D  
**FS/1090/1490** Dual Voltage Coil: 900/450 mA @ 12/24 VDC  
**1290/2490** Dual Voltage Coil: 900/450 mA @ 12/24 VDC

**UL** US LISTED Auxiliary Locks  
**UL10C** Positive Pressure Compliant  
**UBC** Classified in accordance with Uniform Building Code standard 7-2 "Fire Test for Door Assemblies"

<b>FS23MIV</b>	Dual failsafe	<b>350.00</b>
<b>1091AIV</b>	Failsafe	<b>340.00</b>
<b>1091ADLIV</b>	Dead locking, failsafe	<b>400.00</b>
<b>1291AHV</b>	Failsecure	<b>400.00</b>
<b>1490AIV</b>	Fits 1-1/2" frame (non UL), failsafe	<b>400.00</b>
<b>2490AHV</b>	Failsecure. Fits 1-1/2" frame (non UL), failsecure	<b>475.00</b>
<b>V</b>	628 Aluminum Finish (standard)	
<b>WD</b>	Faceplate for wood frames	<b>Add 40.00</b>

**SPECIAL FINISHES Add to List**

<b>Y</b>	335 Black	<b>36.00</b>
<b>Plated Architectural Finishes</b>		
<b>Special order - no cancellations, no return</b>		
<b>C</b>	605 Bright Brass	<b>78.00</b>
<b>D</b>	606 Dull Brass	<b>78.00</b>
<b>F</b>	611 Bright Bronze	<b>78.00</b>
<b>G</b>	612 Satin Bronze	<b>78.00</b>
<b>H</b>	613 Oil Rubbed Bronze	<b>78.00</b>
<b>P</b>	625 Bright Chrome	<b>78.00</b>
<b>Q</b>	626 Dull Chrome	<b>78.00</b>
<b>U</b>	630 Stainless Steel	<b>78.00</b>



**HEAVY DUTY SPACE SAVER® MORTISE BOLT LOCKS**

**AK LIST**



1190A failsafe, 0.7Amp @ 24VDC  
 2090A failsecure, 2.5 Amp In rush, 0.4 Amp seated @ 24VDC,  
 3090 - 0.7 Amp locking coil, 1.4 Amp release coil, 3/4" bolt, 3/4" throw, 24VDC

<b>1190AU</b>	Failsafe	<b>400.00</b>	<b>2090AU</b>	Failsecure	<b>500.00</b>
			<b>3090AU</b>	Failsecure	<b>600.00</b>

Standard Finish: **U** 630 Dull Stainless Steel  
 Specialty Lock Applications available by request

**UL** US LISTED Auxiliary Locks  
**UL10C** Positive Pressure Compliant  
**UBC** Classified in accordance with Uniform Building Code standard 7-2 "Fire Test for Door Assemblies"

**PANICLOK EXIT DEVICE RELEASE**

**AK LIST**



For Dor-O-Matic and Kawneer Exit Device  
**Voltage:** 24VDC, 2.5 A Inrush, .4A seated

<b>PD2090ALU</b>	LH/RHR failsecure	<b>500.00</b>
<b>PD2090ARU</b>	RH/LHR failsecure	<b>500.00</b>

Standard Finish: **U** 630 dull stainless steel

**UL** US LISTED Auxiliary Locks

**OPTIONS Add to List**

<b>B</b>	Bolt position sensor, SPDT	<b>48.00</b>
<b>D</b>	Door position sensor, SPDT	<b>48.00</b>
<b>BR64XL</b>	Rectifier for AC Operation	<b>20.00</b>



**SECURITY DOOR CONTROLS**  
 801 Avenida Acaso • Camarillo, CA 93012  
 Email: Service@sdcsecurity.com • www.sdcsecurity.com

Price List Effective February 15, 2009