

917 INDOOR EntryCheck™

JK LIST



917U 120 user codes, 1 to 6 digits in length, programmable for individual or simultaneous control of 1 relay output and 4 voltage outputs momentary, timed or latching. Automatic time-out, REX input, duress alarm, forced entry alarm, 3 LEDs. **220.00**

ELECTRICAL SPECIFICATIONS

Voltage: 12/24 VAC/DC

Current: 20 mA @ rest, 120 mA maximum

Outputs: Relay 1 - SPDT, 6 Amps @ 30VDC.

Outputs 1,2,3,4 - Switch to common, 500mA @ 12VDC

SPECIFY FINISH

Add to List

U	630 Stainless Steel (standard)	N/C	H	613 Oil Rubbed Bronze	100.00
C	605 Bright Brass	100.00	P	625 Bright Chrome	100.00
D	606 Dull brass	100.00			

OPTIONS

Add to List

TR12 Plug in power supply (optional) **72.00**
 120 VAC primary, secondary screw terminals with ground terminal
 Output 1: Fused unregulated 12VDC @ 780mA
 Output 2: Regulated 12VDC @ 150mA

925 OUTDOOR EntryCheck™

JK LIST



925 Outdoor keypad with 480, 1-6 digit user codes for activation of 2 relay outputs programmable to activate separately or simultaneously for timed or latching applications. Two solid state outputs are programmable to signal two of the following: forced entry, door ajar, keypad lockout, alarm shunt, request-to-exit, relay 1 disable or keypad active. Additional features include timed anti-passback and two LEDs. **500.00**

ELECTRICAL SPECIFICATIONS

Voltage: 12/24 VAC/DC

Current: 10 mA typical, 150 mA maximum

Outputs: Relay 1 - Form "C", 5 Amps @ 24VDC

Relay 2 - Form "C", 1 Amp @ 24 VDC

Outputs 3 and 4 - Switch to common, 100mA @ 30VDC

Operating Temperature: -20 degrees to +130 degrees F

Operating Humidity: 5% to 95% non-condensing

Housing: 4"W x 5.5"H x 3"D

928 INDOOR EntryCheck™

JK LIST



928 Keypad with 480, 1-6 digit user codes for activation of 2 relay outputs programmable to activate separately or simultaneously for timed or latching applications. Two solid state outputs are programmable to signal two of the following: forced entry, door ajar, keypad lockout, alarm shunt, request-to-exit, relay 1 disable or keypad active. Additional features include timed anti-passback and two LEDs. **220.00**

ELECTRICAL SPECIFICATIONS

Voltage: 12/24 VAC/DC

Current: 10 mA typical, 150 mA maximum

Outputs: Relay 1 - Form "C", 5 Amps @ 24VDC

Relay 2 - Form "C", 1 Amp @ 24 VDC

Outputs 3 and 4 - Switch to common, 100mA @ 30VDC

Operating Temperature: -20 degrees to +130 degrees F

Operating Humidity: 5% to 95% non-condensing

Housing: 3"W x 5"H x 3"D



SECURITY DOOR CONTROLS
 3580 Willow Lane • Westlake Village, CA 91361
 Email: Service@sdcsecurity.com • www.sdcsecurity.com

Price List Effective March, 2010