

**Proprietary Verbal Exit Instructions with Alarm Tone and 3/4" Digital Countdown Display**

**Standard features include:** 12/24VDC voltage sensing input, delay electronics packaged on a 3-gang wall plate for recessed wall mounting or surface wall mounting with optional junction box. Features include: 15 or 30 second exit delay, 1 or 2 second nuisance delay. Keypad for violation reset, momentary bypass and on-off; Voice Annunciation and digital countdown display with door open indicator. Status and remote control inputs are standard.



12VDC / 24VDC @ 200 mA Max.

- Doors **WITH** latch assemblies are sensor activated and do not require power transfer or trigger switch in exit device. Where preferred a trigger switch may be added to the exit device for manual activation in lieu of door movement activation.
- Doors **WITHOUT** latches require a non-latching Request-to-Exit Bar PSB560 Sure Exit® or MSB550 Switch Bar (see page 58). Also compatible with standard EMLock's see page 44.



**101-DE**

**DELAYED EGRESS CONTROLLER (1 per opening, single or pairs)**

<b>101-DE</b>	Wall mount controller with keypad control and reset, 200 mA @ 12/24 VDC	<b>750.00</b>
<b>101-KDE</b>	Wall mount controller with both key switch and keypad control and reset, 200 mA @ 12/24 VDC	<b>850.00</b>



**101-KDE**

**MAGNETIC LOCK WITH INTEGRATED ACTIVATION SENSOR**

**Specify 2 for pair of doors**

<b>1511DEV</b>	Single, 1650 lbs holding force, 670/350 mA @12/24 VDC	<b>475.00</b>
<b>1571DEV</b>	Single, 1200 lbs holding force Energy Saver, 250/125 mA @12/24 VDC	<b>450.00</b>
<b>1581DEV</b>	Single, 650 lbs holding force, 440/220 mA @12/24 VDC	<b>375.00</b>

**Outdoor Locks**

<b>1575DEU</b>	Single outdoor magnetic lock with magnetic bond sensor	<b>450.00</b>
<b>1576DEU</b>	Single face drilled outdoor magnetic lock with magnetic bond sensor	<b>450.00</b>



**101-DE with DEC-J**

**MAGNETIC LOCK FINISH**

<b>V</b>	628 Clear Anodized Aluminum (Standard)	<b>N/C</b>
<b>Y</b>	Black Anodized	Single <b>60.00</b>

**Powder Coat Finishes**

*(a coating electrostatically applied to form a hard finish, that is tougher than conventional paint)*


<b>X</b>	Dark Bronze Powder Coat Painted (313/613 Equal)	Single <b>60.00</b>
----------	---	---------------------



**101-1AK**

**OPTIONAL MONITORING**

<b>B</b>	Magnetic bond sensor, indicates locked with full holding force, low holding force, unlocked, tampering and obstructions. (1581DE SPST only)	<b>60.00</b>
<b>D</b>	Door position sensor, indicates door open and door closed. Commonly used to verify egress after alarm and exit delay activation. (D) Door position sensor not available with 1581, 1575 and 1576	<b>40.00</b>



**DEC-J**

**OPTIONAL HARDWARE**

<b>101-1AK</b>	Outdoor reset with LED and Audible annunciator. 2-gang outdoor box required (Interior 101-DEC and 1575 or 1576 outdoor magnetic lock required)	<b>300.00</b>
<b>DEC-J</b>	3 Gang Interior surface mount box for 101-DEC	<b>90.00</b>
<b>SHD-J</b>	Shroud for surface mount box DEC-J outdoor use	<b>60.00</b>



**SHD-J End View**

**Mounting Kits & Angle Brackets - See pages 46 through 48**

Price List Effective February 15, 2009

**SECURITY DOOR CONTROLS**  
801 Avenida Acaso • Camarillo, CA 93012  
Email: Service@sdsecurity.com • www.sdsecurity.com

