

Proprietary Verbal Exit Instructions with Alarm Tone and 3/4" Digital Countdown Display

Standard features include: 12/24VDC voltage sensing input, delay electronics packaged on a 3-gang wall plate for recessed wall mounting or surface wall mounting with optional junction box. Features include: 15 or 30 second exit delay, 1 or 2 second nuisance delay. Keypad for violation reset, momentary bypass and on-off; Voice Annunciation and digital countdown display with door open indicator. Status and remote control inputs are standard.



12VDC / 24VDC @ 200 mA Max.

• Doors **WITH** latch assemblies are sensor activated and do not require power transfer or trigger switch in exit device. Where preferred a trigger switch may be added to the exit device for manual activation in lieu of door movement activation.

• Doors **WITHOUT** latches require a non-latching Request-to-Exit Bar PSB560 Sure Exit® or MSB550 Switch Bar (see page 58). Also compatible with standard EMLock's see page 44.

Price List Effective March, 2010



101-DE

DELAYED EGRESS CONTROLLER (1 per opening, single or pairs)

101-DE	Wall mount controller with keypad control and reset, 200 mA @ 12/24 VDC	750.00
101-KDE	Wall mount controller with both key switch and keypad control and reset, 200 mA @ 12/24 VDC	850.00



101-KDE

MAGNETIC LOCK WITH INTEGRATED ACTIVATION SENSOR

Specify 2 for pair of doors

1511DEV	Single, 1650 lbs holding force, 670/350 mA @12/24 VDC	475.00
1571DEV	Single, 1200 lbs holding force Energy Saver, 250/125 mA @12/24 VDC	450.00
1581DEV	Single, 650 lbs holding force, 440/220 mA @12/24 VDC	375.00

Outdoor Locks

1575DEU	Single outdoor magnetic lock with magnetic bond sensor	450.00
1576DEU	Single face drilled outdoor magnetic lock with magnetic bond sensor	450.00



101-DE with DEC-J

MAGNETIC LOCK FINISH

V	628 Clear Anodized Aluminum (Standard)	N/C
X	Dark Bronze (313/613 equal)	Single 60.00
Y	Black Anodized	60.00

OPTIONAL MONITORING


B	Magnetic bond sensor, indicates locked with full holding force, low holding force, unlocked, tampering and obstructions. (1581DE SPST only)	60.00
D	Door position sensor, indicates door open and door closed. Commonly used to verify egress after alarm and exit delay activation. (D) Door position sensor not available with 1581, 1575 and 1576	40.00



101-1AK

OPTIONAL HARDWARE

101-1AK	Outdoor reset with LED and Audible annunciator. 2-gang outdoor box required (Interior 101-DEC and 1575 or 1576 outdoor magnetic lock required)	300.00
DEC-J	3 Gang Interior surface mount box for 101-DEC	90.00
SHD-J	Shroud for surface mount box DEC-J outdoor use	60.00



DEC-J



SHD-J End View

Mounting Kits & Angle Brackets - See pages 46 through 48

SECURITY DOOR CONTROLS
3580 Willow Lane • Westlake Village, CA 91361
Email: Service@sdsecurity.com • www.sdsecurity.com

