

Function: 7200 series locksets are locked on the outside and unlocked from the exterior by an access control or mechanical key. The inside lever is always operable for uninhibited egress.

Request-to-Exit Output: Standard with all SDC brand Z7200 locksets. SPDT, 3 Amps @ 30VDC

Features

- Clutch for vandal resistance
- Choice of failsecure or failsafe mode
- Dual 12/24 VDC
- REX output: Z7200 standard; S and ZS7200 optional
- 'C' type keyway
- Independent lever power return springs

Specifications


- Dual Voltage, 600/300 mA @ 12/24VDC
- Exceeds ANSI A156-2-4000 Grade 1
- 0.5625" latchbolt
- 2.75" Backset
- 4.875 strike ANSI A115.2



Z7250G



Z7250E



S7250ROH



S7250SPA



I-CORE



Electrically Controlled Single Point
Locks & Latches, 3 Hr A Label Fire Doors



3773-0324-104
CSFM



SPECIFY MODEL

LIST

Locks supplied by SDC**LIST**

Z7250	SDC Failsafe, with REX Output	396.00
Z7252	SDC Failsecure, with REX Output	396.00
ZS7250	Schlage, Failsafe	460.00
ZS7252	Schlage, Failsecure	460.00

Lockset provided by customer for electrification

S7250	Schlage, Failsafe	110.00
S7252	Schlage, Failsecure	110.00

SPECIFY LEVER TRIM

SDC Lever Trim

G	Galaxy
E	Eclipse

Schlage Lever Trim

ROH	Rhodes	N/C
SPA	Sparta	N/C

SPECIFY FINISH

C	605 Bright Brass	H	613 Oil Rubbed Bronze	N/C
D	606 Dull Brass	P	625 Bright Chrome	N/C
F	611 Bright Bronze	Q	626 Dull Chrome	N/C
G	612 Dull Bronze			N/C

OPTIONAL CYLINDER and I-CORES

Add to List

Optional Cylinder

Keyed different is standard

6PKA	Keyed alike	N/C
-------------	-------------	------------

Interchangeable Core (SDC Brand Locks Only)

IC6P-KD	6 pin I-Core, small format, keyed different	50.00
IC6P-KA	6 pin I-Core, small format, keyed alike	50.00

OPTIONAL STRIKE PLATES

Add to List

4.875" ANSI strike is standard unless specified otherwise

S2	2.25" ANSI strike with square corners	N/C
S3	2.25" Full lip strike with square corners (for wood frames)	N/C

OPTIONAL LATCH AND BACKSET ASSEMBLIES

Add to List

L75	0.75" Latchbolt assembly (required for pairs of 3 Hr, A label, Fire Rated Doors)	16.00
B2	2.375" backset latch assembly with 0.5625" Latch	N/C

OPTIONS & ACCESSORIES

Add to List

REX	For S7200 and ZS7200, request-to-exit output, SPDT, 3 Amps @ 30VDC	76.00
030736-00-70	Drill guide for locating 5/16" thru-bolt holes	25.00