

Auto EntryControl™ FAQs

1. I currently use model XXX, what makes your unit different?

One-button setup, Non-handed, Best warranty on the market, Best price with the most features, Momentary closing force prior to unlocking for electric strike application(rare feature).

2. What configurations do you offer? What sizes? What finishes?

Size- 36", 42", 48" or custom

Finish- Standard Aluminum or Dark Anodized Aluminum

3. Can I use 2 single units for a double door?

Yes

4. Does your unit have an onboard power supply to control electrified hardware? How much power is available and at what rating?

Yes, 24v output & sequencer for mags/strikes, 500 mA total

5. When would I use a door-mounted sensor? Is it required by ADA?

We recommend the IR Presence Sensor which provides automatic, non-contact reactivation if someone remains in the door opening path while the door is closing. Not required by ADA.

6. Do I need safety sensors for your unit?

No, not required for Low Energy Operators

7. Do you have a fire alarm input?

Yes

8. Can your unit provide additional force on closing for external doors?

Power close option controls exterior openings that may require additional force. For example, wind conditions. Saves on heating and cooling costs.

9. Does your unit allow for external activation sensors to be disabled during off hours?

If so, how?

Yes, by switching to "Night Mode". This disables normal powered operation by external activation sensors, but can be configured to receive activation signals from a secure activation device.

10. Do you have an external key switch?

Not built in, but an external key switch can be easily wired in.

11. How much does it cost?

List price apx \$2,200

12. How do I adjust opening/closing/hold open times?

Simply on the Adjustment Time Board by holding down on each for the length of desired time

Opening Time Adjustment (3-10 sec)

Closing Time Adjustment (3-10 sec)

Hold Open Time (0-30 sec)

13. What's the maximum door weight your operator can handle?

438lb. For 36" Door w/ Push Arm, ANSI requires 200lb and we exceed much higher.

14. Is your device UL listed?

Yes

15. How many cycles has it been tested to?

1.3 million to a fully closed position. Retriggered during close cycle for an addition 500,00 cycles.



The lock behind your system

(800) 413-8783 ■ WWW.SDCSECURITY.COM