



1490 / 2490 Series

Narrow Right Angle
Electric Bolt Locks

Designed and patented by SDC, Spacesaver® right angle bolt locks represent a fundamental innovation in electric locking technology for access control applications.

Spacesaver® bolts project at right angles to the lock mechanism, allowing installation of Spacesaver® locks, by means of a simple mortise cutout, in virtually any standard frame, or in most door lock stiles. With the entire lock concealed, aesthetic acceptability is complete, security is greater and installation in old or new construction is fast, easy and economical.

1490A and 2490A models are designed to fit in narrow 1½" frame or door stile.

- Concealed mortise right angle design
- Stainless steel bolt
- Specification grade solenoid
- Automatic relock
- Field adjustable and bidirectional automatic relock ball switch
- Mounting tabs included
- Field selectable dual voltage
- Voltage and current spike protection
- Power regulator included

ORDERING GUIDE

	FUNCTION		OPTIONS	
		I		D
		H		B
1490A		I	V	D B
1490A			V	
2490A			Y	
MODEL			D	
			C	
			G	
			F	
			H	
			Q	
			P	
			U	
			S	
			FINISH	

NOT REQUIRED

EXAMPLES

1490AIV	Narrow Right Angle Bolt Lock, Failsafe, 628	483.00
1490AIVDB	Narrow Right Angle Bolt Lock, Failsafe, 628, DPS, BPS	613.00
1490AIY	Narrow Right Angle Bolt Lock, Failsafe, 335	527.00
2490AHV	Narrow Right Angle Bolt Lock, Failsecure, 628	572.00
2490AHVDB	Narrow Right Angle Bolt Lock, Failsecure, 628, DPS, BPS	702.00


COMPONENT CONSIDERATIONS

With a robust toolbox of over 35,000 SDC access & control components at your fingertips, you can add additional components to complement the products you're ordering and assemble a turnkey solution for almost any controlled door opening system imagined.



Keypads & Readers

[CLICK TO VIEW](#)



Exit Switches & Sensors

[CLICK TO VIEW](#)



Power Controllers

[CLICK TO VIEW](#)



Door Controls & Backup Batteries

[CLICK TO VIEW](#)



Remote Control Consoles

[CLICK TO VIEW](#)



Door Prop Alarms & Annunciators

[CLICK TO VIEW](#)

1490/2490 CONFIGURATION 1 of 1

MODEL		LIST \$
	● ○ ○ ○	
1490A	Narrow Right Angle Bolt Lock, Failsafe	483.00
2490A	Narrow Right Angle Bolt Lock, Failsecure	572.00

FUNCTION		ADD TO LIST
	○ ● ○ ○	
I*	Failsafe	N/C
H**	Failsecure	N/C

*For 1490A failsafe models only.

**For 2490A failsecure models only.

FINISH		ADD TO LIST
	○ ○ ● ○	
V	628 Dull Aluminum <small>Standard</small>	N/C
Y	335 Dull Black	44.00
D	606 Dull Brass	92.00
C	605 Bright Brass	92.00
G	612 Dull Bronze	92.00
F	611 Bright Bronze	92.00
H	613 Dark Oil Rubbed Bronze	92.00
Q	626 Dull Chrome	92.00
P	625 Bright Chrome	92.00
U	630 Dull Stainless	92.00
S	629 Bright Stainless	92.00

OPTIONS		ADD TO LIST
	○ ○ ○ ●	
D	Door Position Status (DPS)	65.00
B	Bolt Position Status (BPS)	65.00