

430 Series Mushroom Exit Switches

The SDC 430 Heavy Duty Industrial Series incorporates a 1 1/2" round mushroom button with heavy duty contacts. The assembly is capable of withstanding high impact and is ideal for heavy duty high frequency use.



The SDC 432KLDUR and 432KUR latches when depressed and must be reset with the built-in-key. Applications include alarm, panic alarm and emergency door release where systems are restored by authorized personnel only. Red Button Standard

FEATURES

- 1.5" Mushroom Exit Switches
- Heavy Duty to Withstand Impact
- Water Resistant Contacts
- Ideal for High Frequency Use
- Green Button standard - Specify R for Red Button

SPECIFICATIONS

Contact	6 Amp @ 30VDC Resistive
Wire Connection	Screw Terminals
1 Gang	2 7/8" x 4 1/2" x 20 Ga.
Narrow	1 3/4" x 4 1/2" x 20 Ga.
2 Gang	4 1/2" x 4 1/2" x 20 Ga.
Weight	0.5 lbs



430



430N


MODELS

NARROW

431CN	AA (On/Off) NC SPST	None
431ON	AA (On/Off) NO SPST	None
432CN	Momentary NC SPST	EXIT
432ON	Momentary NO SPST	EXIT
432KNUR	Latching/ key reset DPST	RED/None
434N	Momentary DPST	EXIT
435N	AA (On/Off) DPST	None

1 GANG

431C	AA (On/Off) NC SPST	None
431O	AA (On/Off) NO SPST	None
432C	Momentary NC SPST	EXIT
432O	Momentary NO SPST	EXIT
432KUR	Latching/ key reset DPST	RED/None

 432KLDUR	Lockdown key reset DPST	UL 294 LOCK-DOWN
432KLDURL2	Lockdown key reset DPST, 1 red, 1 green LED	LOCK-DOWN
434	Momentary DPST	EXIT
435	AA (On/Off) DPST	None

2 GANG

433	Momentary with Electronic Timer Module, Adj. 1-60 Seconds. 12/24V AC/DC, SPDT 2A Contact	EXIT
------------	--	------





HOW TO ORDER

1| SPECIFY MODELS

NARROW

431CN	AA (On/Off) NC SPST	None
431ON	AA (On/Off) NO SPST	None
432CN	Momentary NC SPST	EXIT
432ON	Momentary NO SPST	EXIT
434N	Momentary DPST	EXIT
435N	AA (On/Off) DPST	None

1 GANG

431C	AA (On/Off) NC SPST	None
431O	AA (On/Off) NO SPST	None
432C	Momentary NC SPST	EXIT
432O	Momentary NO SPST	EXIT
434	Momentary DPST	EXIT
435	AA (On/Off) DPST	None

2 GANG

433	Momentary with Electronic Timer Module, Adj. 1-60 Seconds. 12/24V AC/DC, SPDT 2A Contact	EXIT
------------	---	------

2| SPECIFY FINISHES

U 630 Stainless Steel - STANDARD	
C 605 Bright Brass	D 606 Dull Brass
H 613 Oil Rubbed Bronze	P 625 Bright Chrome

3| SPECIFY LED OPTIONS

L1G 1 Green LED	LT Tri-color LED - Red, Green, Amber
L1R 1 Red LED	
L2 1 Red, 1 Green LED	R Red Button in lieu of green

LATCHING MODELS

NARROW

432KNUR	Narrow	RED/
	Latching/ key reset DPST	None
Stainless Steele Finish Standard - contact factory for special finish		

1 GANG

432KUR	1 Gang	RED/
	Latching/ key reset DPST	None
432KLDUR	1 Gang	RED/
	Lockdown key reset DPST	LOCKDOWN
	UL 294	
432KLDURL2	1 Gang	RED/
	Lockdown key reset DPST,	LOCKDOWN
	one red, one green LED	
Stainless Steele Finish Standard - contact factory for special finish		