

# 450 Vandal Resistant Series Exit Switches

The **SDC 450 Series** incorporates a 1/4" thick aluminum faceplate and an all stainless steel button. The assembly will resist the impact of a hammer blow. In addition, security spanner mounting screws are concealed by tamper resistant aluminum plugs to inhibit tampering.

## PNEUMATIC TIME DELAY

The 453P includes a 1 to 180 second pneumatic timer for delayed re-locking. Where preferred, the 10TD Electronic Mini Timer may be specified for use with the standard 452 model.



450



450N



## FEATURES

- Stainless Steel Button - 1/4" Thick Aluminum Plate
- Security Screws



## SPECIFICATIONS

<b>Button</b>	Round Dull Stainless Steel button, 1/2"
<b>Contact</b>	6 Amp @ 30VDC Resistive
<b>Wire Connection</b>	451/452: 6", 20 Gauge 453P: Screw terminals
<b>1 Gang</b>	2 7/8" x 4 1/2" x 1/4"
<b>Narrow</b>	1 3/4" x 4 1/2" x 1/4"
<b>Weight</b>	0.5 lbs



## MODELS

### 1 GANG

**451V** AA (On/Off) SPDT



**452V** Momentary SPDT

**453PV** Integrated Pneumatic Timer  
Adj. 1-180 sec. DPST Contact

### NARROW SERIES

**451NV** AA (On/Off) SPDT



**452NV** Momentary SPDT

**453PNV** Integrated Pneumatic Timer  
Adj. 1-180 sec. DPST Contact



