
### COMMON APPLICATIONS

# Automated Magnetic Lock Access Control





# 1 AUTO Series

#### Low Energy Swing Door Operators

Low Energy owing boor operators		
AUTOS136V	Push Arm, 36" Opening	
AUTOS236V	Pull Arm, 36" Opening	
AUTO-IR36Y	Presence Sensor	
- 1	Single button, self-	

•

- Single button, selftuning setup Built-in 1 Amp power
- supply
- Onboard lock sequencing

# **4** PSB560 Series

#### **Pressure Sense Bars**

PSB560V36	36" Opening
PSB560V42	42" Opening
PSB560V48	48" Opening
PURIFICATION PROVIDENT	<ul> <li>Tri-failsafe</li> </ul>
	Heavy duty aluminum     extrusion
	<ul> <li>Metal end caps</li> </ul>



### Premium Electromagnetic Locks

1511V	Single EMLock
1512V	Double EMLock
	<ul> <li>1,650lb holding force</li> <li>Auto-sensing dual voltage</li> </ul>
	<ul> <li>Interlocking quick mount</li> </ul>



#### Indoor/Outdoor Digital Keypads

920	Self Contained	
920P	Self Contained w/Prox	
920PW	Weigand Output	
	Single gang wall or surface     mount	
	Heavy cast vandal resistant housing	
	• 500 users	

# 5 460 Series

### **Capacitive Touch Sensors**

463NU	Narrow
463U	Single Gang
© PUSH TO PUSH TO	Integrated adjustable
	timer



 Adjustable timer or alternate action