## **IPRW Series**

Wiegand Readers



# SDC's IPRW series is the perfect companion for our IPPro® Controller.

The IPRW wiegand proximity reader is a sleek, sophisticated reader that will interface with most access control systems. It combines a 125KHz HID-compatible proximity reader and standard 26-bit wiegand output with compact design for surface or mullion mounting. An IP67 rated housing makes the IPRW reader suitable for use in indoor or outdoor environments. An LED indicator lights red to indicate power, or green to indicate an authorized access (controlled externally by host). The audible annunciator will indicate when a card is present or can be controlled externally. When paired with SDC's IPPro® Single Door Controller, compatibility is guaranteed.



IPRW300 Weigand Reader, Mullion MountIPRW500 Weigand Reader, Single Gang Mount



- Entry / Exit reader for IPPro controller
- Standard 26-bit weigand output
- HID proximity compatible (125 kHz)
- · Black & white snap-on covers included
- Mullion or single gang mount models







### **SPECIFICATIONS**

	IPRW300	IPRW500
Housing	Indoor/Outdoor (IP67)	Indoor/Outdoor (IP67)
	w/ Potted Electronics	w/ Potted Electronics
Dimensions	3 <sup>13</sup> / <sub>64</sub> "W x 1 <sup>45</sup> / <sub>64</sub> "H x <sup>45</sup> / <sub>64</sub> "D	4³%4″W x 3″H x ¹³/₃2″D
Input	5-16 VDC	5-16 VDC
Current	30mA Typical, 75mA Maximum	30mA Typical, 75mA Maximum
Output	26-bit Wiegand	26-bit Wiegand
HID Compatible	125 Khz RFID	125 Khz RFID
Read Range	Up to 5"	Up to 8"
Cable Distance to Host (Max)	328 ft @ 12 VDC	328 ft @ 12 VDC
	100 ft @ 5 VDC	100 ft @ 5 VDC
Operating Temparature	-40°F to +149°F	-40°F to +149°F
Weight	2 lbs	2 lbs

### HOW TO ORDER

#### FOLLOW STEPS FOR ORDERING

Designates optional step

1| SPECIFY MODEL

IPRW300 Weigand Reader, Mullion Mount

IPRW500 Weigand Reader, Single Gang Mount

STEP NUMBER:	1
ORDERING EXAMPLE:	IPRW500



#### **RELATED PRODUCTS**

#### IP BASED ACCESS CONTROL

SDC's IPPro® line of IP-based access controllers allows expansion from one standalone door up to a 100-door "Grid." It's like having a local area network for your doors without all the headaches of an enterprise system. Every IPPro® controller comes with secure, built-in software to manage up to 32 doors from any standard web browser to allow for real-time monitoring, user management and audit trail up to 5,000 events. Or, download our FREE PLUS PC-Client software to control up to 100 doors from a single PC. IPPro® PLUS is a role-based access control software suite with different interface modules. SDC's IPPro® Injectors and Splitters are also available to help create a complete solution.





PROX CARDS, FOBS & TAGS

HID1326-10 Proximity Card Pack, HID Compatible, Quantity 10

HID1326-25 Proximity Card Pack, HID Compatible, Quantity 25

HID1326-100 Proximity Card Pack, HID Compatible, Quantity 100

HID1346-10 Proximity Key Fob Pack, HID Compatible, Quantity 10

HID1346-100 Proximity Key Fob Pack, HID Compatible, Quantity 100

PTAG-10 Proximity Disc Tag Pack, HID Compatible, Quantity 10

PTAG-25 Proximity Disc Tag Pack, HID Compatible, Quantity 25

