

100 / 200 Series

Conventional Direct Throw Electric Bolt Locks

Coventional direct throw bolt locks are the most basic bolt locks available. All SDC bolt locks are available in failsafe or failsecure operation. Not recommended for wood applications.

110I and 210H models feature a bolt assembly that is adjustable forward up to 1" past the face plate to accommodate wide door gaps or special applications

160I and 260H models feature the same adjustable bolt assembly and are also equipped with an automatic relock ball switch. Automatic relock ball switches keep the bolt retracted while the door is open. The door depresses the ball switch on closure, causing the bolt to project automatically, locking the door. Additionally, ball switches are field adjustable to compensate for wide door gap and bidirectional to permit use on swinging and sliding doors.

180Al and 280AH models feature a universal surface mount design with an automatic relock switch to provide controlled access of doors, closets and cabinets.

- · Conventional direct throw design
- · Stainless steel bolt
- · Field selectable dual voltage
- Voltage and current spike protection

MODEL		LIST \$
110IV	Direct Throw Mortise Bolt Lock, Failsafe, 628	228.00
210HV	Direct Throw Mortise Bolt Lock, Failsecure, 628	228.00
160IV	Direct Throw Mortise Bolt Lock, Auto-Relock, Failsafe, 628	305.00
260HV	Direct Throw Mortise Bolt Lock, Auto-Relock, Failsecure, 628	305.00
180AIV	Direct Throw Surface Mount Bolt Lock, Failsafe, 628	344.00
280AHV	Direct Throw Surface Mount Bolt Lock, Failsecure, 628	344.00

SDC LIT-PL23_020325 | **107**