

1561S Series


Surface Electromagnetic Shear Locks

SDC's HiShear® electromagnetic shear locks are designed, engineered and built in America for openings that require an architecturally superior appearance. Long recognized as a cut above alternatives on the market, SDC shear locks provide high security with a failsafe locking mechanism to meet a variety of door opening applications.

1561S models are surface mounted to the push side of an out-swing door.

- · Surface mount design
- · Floating armature assembly
- Special alloy steel shear tabs
- Auto-sensing dual voltage
- Door alignment relock sensor
- Adjustable lateral and vertical alignment
- · Noise dampeners

ORDERING GUIDE



NOT REQUIRED

EXAMPLES

1561SV	Surface Shear Lock, Integrated Electronics, 2000lbs, 628	1,299.00
1561SVD	Surface Shear Lock, Integrated Electronics, 2000lbs, 628, DPS	1,363.00
1561SVDB	Surface Shear Lock, Integrated Electronics, 2000lbs, 628, DPS. BAS	1,503.00
1561SVDBL	Surface Shear Lock, Integrated Electronics, 2000lbs, 628, DPS. BAS, LED	1,525.00
1561SY	Surface Shear Lock, Integrated Electronics, 2000lbs, 335	1,401.00

COMPONENT **CONSIDERATIONS**

With a robust toolbox of over 35,000 SDC access & control components at your fingertips, you can add additional components to complement the products you're ordering and assemble a turnkey solution for almost any controlled door opening system imagined.



Keypads & Readers Page 112-116



Egress Devices



Exit Switches & Sensors Pages 134-145





Emergency Door Releases Page 146



Power Controllers Pages 153-164



Door Controllers Page 165



Remote Control Consoles





Door Prop Alarms & Annunciators Page 168-169

CONFIGURATION 1561S

MODEL	●00	LIST\$
1561S	Surface Shear Lock, Integrated Electronics, 2000lbs	1,299.00

FINISH	0•0	ADD TO LIST
V	628 Dull Aluminum & Standard	N/C
Υ	335 Dull Black	102.00
С	605 Bright Brass	130.00
X	710 Dark Bronze	102.00
Q	626 Dull Chrome	242.00
P	625 Bright Chrome	242.00

OPTIONS	00•	ADD TO LIST
D	Door Position Status (DPS)	64.00
В	Bond Alert Status (BAS)	140.00
L*	Visual Status Indicator (LED)	22.00

^{*}Mounts separately through the frame and may be used to indicate lock is enegized or wired to monitoring contacts.