



1561TJ Series

Surface Top Jamb
Electromagnetic Shear Locks

SDC's HiShear® electromagnetic shear locks are designed, engineered and built in America for openings that require an architecturally superior appearance. Long recognized as a cut above alternatives on the market, SDC shear locks provide high security with a failsafe locking mechanism to meet a variety of door opening applications.

1561TJ models are surface mounted to the pull side of an in-swing door. For metal door and frame, glass door with top rail and metal frame, or wood door and frame. This mounting configuration eliminates the need for cumbersome and unsightly top jamb Z brackets normally associated with pull side mounted of magnetic locks.

- Surface mount design
- Floating armature assembly
- Special alloy steel shear tabs
- Auto-sensing dual voltage
- Door alignment relock sensor
- Adjustable lateral and vertical alignment
- Noise dampeners

ORDERING GUIDE

			FINISH	
			V	
			Y	
			C	
			X	
			P	
			Q	
MODEL	1561TJ	V	D B	
			D	
			B	
			L	
			OPTIONS	

NOT REQUIRED

EXAMPLES

1561TJV	Surface Top Jamb Shear, Integrated Electronics, 2000lbs, 628	1,299.00
1561TJVD	Surface Top Jamb Shear, Integrated Electronics, 2000lbs, 628, DPS	1,363.00
1561TJVDB	Surface Top Jamb Shear, Integrated Electronics, 2000lbs, 628, DPS. BAS	1,503.00
1561TJY	Surface Top Jamb Shear, Integrated Electronics, 2000lbs, 335	1,401.00
1561TJX	Surface Top Jamb Shear, Integrated Electronics, 2000lbs, 710	1,401.00

COMPONENT CONSIDERATIONS


With a robust toolbox of over 35,000 SDC access & control components at your fingertips, you can add additional components to complement the products you're ordering and assemble a turnkey solution for almost any controlled door opening system imagined.



Keypads & Readers
Page 112-116



Egress Devices
Pages 129-133



Exit Switches & Sensors
Pages 134-145



Emergency Door Releases
Page 146



Power Controllers
Pages 153-164



Door Controllers
Page 165



Remote Control Consoles
Pages 166-167



Door Prop Alarms & Annunciators
Page 168-169

1561TJ CONFIGURATION 1 of 1

MODEL		LIST \$
1561TJ	Surface Top Jamb Shear Lock, Integrated Electronics, 2000lbs	1,299.00

FINISH		ADD TO LIST
V	628 Dull Aluminum <small>Standard</small>	N/C
Y	335 Dull Black	102.00
C	605 Bright Brass	130.00
X	710 Dark Bronze	102.00
Q	626 Dull Chrome	242.00
P	625 Bright Chrome	242.00

OPTIONS		ADD TO LIST
D	Door Position Status (DPS)	64.00
B	Bond Alert Status (BAS)	140.00
L*	Visual Status Indicator (LED)	22.00

*Mounts separately through the frame and may be used to indicate lock is energized or wired to monitoring contacts.