SDC SureExit[®]



PSB560 Series

Pressure Sense Bars

ORDERING GUIDE

Stable and reliable pressure sense technology. Building codes essentially state that egress through access controlled doors must not require prior knowledge of operational requirements. Meeting this criteria, SDC's patented SureExit® PSB560 series pressure sense bars are designed to release electromagnetic door locks for uninhibited egress. When slight pressure is applied to the non-latching bar, either of the two redundant solid state pressure sensors are actuated causing the electronics to immediately release the electromagnetic door locks.

A third redundant micro switch is automatically activated to release the door if both sensors or the electronics fail. This automatic emergency release switch does not require prior knowledge to find or use. Door operation will continue without the inconvenience of emergency service. **The SDC SureExit® is the only tri-failsafe exit bar** providing unequaled safety and reliability.

- Reliable pressure sense technology
- · Sensor calibration not required
- Quick and quiet operation
- Tri-failsafe
- · Heavy duty aluminum extrusion
- Metal end caps
- High traffic use
- Temperature tolerant
- Narrow, low-profile
- Two outputs
- Auto-sensing dual voltage

	FINISH	
	V	
	Y	
	S	
	U	
PSB560	V	36
MODEL		36
		42
		42 48

EGRESS CONTROLS

EXAMPLES

PSB560V36	Pressure Sense Bar, 628, 36"	439.00
PSB560Y36	Pressure Sense Bar, 335, 36"	439.00
PSB560V42	Pressure Sense Bar, 628, 42"	439.00
PSB560V48	Pressure Sense Bar, 628, 48"	439.00
PSB560U36	Pressure Sense Bar, 630, 36"	594.00

COMPONENT CONSIDERATIONS

With a robust toolbox of over 35,000 SDC access & control components at your fingertips, you can add additional components to complement the products you're ordering and assemble a turnkey solution for almost any controlled door opening system imagined.



Electromagnetic Locks Pages 10-25



Electromagnetic Shear Locks Pages 26-33



Delayed Egress Locks Pages 34-56





Power Transfer Devices Page 152



Power Controllers Pages 153-164

PSB560 CONFIGURATION 1 of 1

	MODEL		$\bullet \circ \circ$	LIST \$
C	PSB560	Pressure Sense Bar		439.00

FINSH	$\bigcirc ullet \bigcirc$	ADD TO LIST
V	628 Dull Aluminum & Standard	N/C
Y	335 Dull Black	N/C
S	629 Bright Stainless	155.00
U	630 Dull Stainless	155.00

LENGTH*	$\bigcirc \bigcirc \bullet$	ADD TO LIST
36	36" Door Opening Østandard	N/C
42	42" Door Opening	N/C
48	48" Door Opening	N/C

* May be field cut.

RELATED PRODUCTS

When you order any SDC products in this section, there are a number of related or complementary products that have proven to work well with your selection.

500GL-KIT	Single Bar Glass Door Mounting Kit and Adhesive for 8-10 Bars	297.00
500GL-MB	Single Bar Glass Door Mounting Kit, No Adhesive	165.00
500-SK*	Shim Kit	32.00

* Used to raise bar from door. Recommended for wood or hollow metal doors with uneven mounting surface.