



# PSB560 Series

Pressure Sense Bars

Stable and reliable pressure sense technology. Building codes essentially state that egress through access controlled doors must not require prior knowledge of operational requirements. Meeting this criteria, **SDC's patented SureExit® PSB560 series pressure sense bars** are designed to release electromagnetic door locks for uninhibited egress. When slight pressure is applied to the non-latching bar, either of the two redundant solid state pressure sensors are actuated causing the electronics to immediately release the electromagnetic door locks.

A third redundant micro switch is automatically activated to release the door if both sensors or the electronics fail. This automatic emergency release switch does not require prior knowledge to find or use. Door operation will continue without the inconvenience of emergency service.

**The SDC SureExit® is the only tri-failsafe exit bar** providing unequalled safety and reliability.

- Reliable pressure sense technology
- Sensor calibration not required
- Quick and quiet operation
- Tri-failsafe
- Heavy duty aluminum extrusion
- Metal end caps
- High traffic use
- Temperature tolerant
- Narrow, low-profile
- Two outputs
- Auto-sensing dual voltage

## ORDERING GUIDE


		FINISH
		V
		Y
		S
		U
PSB560	V	36
MODEL		36
		42
		48
		LENGTH

## EXAMPLES

<b>PSB560V36</b>	Pressure Sense Bar, 628, 36"	<b>401.00</b>
<b>PSB560Y36</b>	Pressure Sense Bar, 335, 36"	<b>401.00</b>
<b>PSB560V42</b>	Pressure Sense Bar, 628, 42"	<b>401.00</b>
<b>PSB560V48</b>	Pressure Sense Bar, 628, 48"	<b>401.00</b>
<b>PSB560U36</b>	Pressure Sense Bar, 630, 36"	<b>543.00</b>


## COMPONENT CONSIDERATIONS

With a robust toolbox of over 35,000 SDC access & control components at your fingertips, you can add additional components to complement the products you're ordering and assemble a turnkey solution for almost any controlled door opening system imagined.




Electromagnetic Locks

[CLICK TO VIEW](#)



Electromagnetic Shear Locks

[CLICK TO VIEW](#)



Delayed Egress Locks

[CLICK TO VIEW](#)



Keypads & Readers

[CLICK TO VIEW](#)



Power Transfer Devices

[CLICK TO VIEW](#)



Power Controllers

[CLICK TO VIEW](#)

## PSB560 CONFIGURATION 1 of 1

MODEL		LIST \$
<b>PSB560</b>	Pressure Sense Bar	<b>401.00</b>

FINISH		ADD TO LIST
<b>V</b>	628 Dull Aluminum <small>Standard</small>	<b>N/C</b>
<b>Y</b>	335 Dull Black	<b>N/C</b>
<b>S</b>	629 Bright Stainless	<b>142.00</b>
<b>U</b>	630 Dull Stainless	<b>142.00</b>

LENGTH*		ADD TO LIST
<b>36</b>	36" Door Opening <small>Standard</small>	<b>N/C</b>
<b>42</b>	42" Door Opening	<b>N/C</b>
<b>48</b>	48" Door Opening	<b>N/C</b>

\*May be field cut.

## RELATED PRODUCTS

When you order any SDC products in this section, there are a number of related or complementary products that have proven to work well with your selection.

<b>500GL-KIT</b>	Single Bar Glass Door Mounting Kit and Adhesive for 8-10 Bars	<b>276.00</b>
<b>500GL-MB</b>	Single Bar Glass Door Mounting Kit, No Adhesive	<b>153.00</b>
<b>500-SK*</b>	Shim Kit	<b>29.00</b>

\*Used to raise bar from door. Recommended for wood or hollow metal doors with uneven mounting surface.