

**SELECTRIC® Pro Locksets** incorporate an SDC manufactured Grade 1 Heavy Duty mortise lockset and vandal resistant clutch mechanism. Proprietary to SDC, SELECTRIC® Pro locksets. All operational attributes are field selectable. In addition, SELECTRIC® Pro locksets retrofit many other mechanical lock brands making them fully compatible with new and retrofit applications.

**FIELD SELECTABLE ATTRIBUTES (SEE DATASHEET FOR SPECIFIC MODELS)**

- Selectable mode, failsafe or failsecure
- Selectable function, locked outside only or both sides
- Selectable voltage, 12 or 24VDC
- Selectable handing



Electrically Controlled Single Point Locks or Latches  
3 Hr A Label Fire Rated Doors



3773-0324:104



**SPECIFY FUNCTION AND MODE**           **LIST**

**SDC Supplied Electrified Lock** (Mortise cylinder not included). SDC Brand 7800 lockset. Clutch for lever trim vandal resistance. \* Less trim - compatible with Schlage trim **\* Less Trim With SDC Trim**



|              |   |               |               |
|--------------|---|---------------|---------------|
| <b>Z7830</b> | Locked both sides, failsafe. Field reversible to failsecure mode.                   | <b>306.00</b> | <b>735.00</b> |
| <b>Z7832</b> | Locked both sides, failsecure. Field reversible to failsafe mode.                   | <b>306.00</b> | <b>735.00</b> |
| <b>Z7850</b> | Locked outside only, failsafe. Field reversible to failsecure mode.                 | <b>306.00</b> | <b>735.00</b> |
| <b>Z7852</b> | Locked outside only, failsecure. Field reversible to failsafe mode.                 | <b>306.00</b> | <b>735.00</b> |
| <b>Z7835</b> | Locked outside and/or inside. Outside failsecure, inside failsafe                   | <b>466.00</b> | <b>849.00</b> |
| <b>Z7870</b> | Locked outside only, failsafe with manual deadbolt for High Security Applications   | <b>406.00</b> | <b>835.00</b> |
| <b>Z7872</b> | Locked outside only, failsecure with manual deadbolt for High Security Applications | <b>406.00</b> | <b>835.00</b> |
| <b>Z7880</b> | Locked outside only, failsafe with manual deadbolt for Privacy Feature              | <b>406.00</b> | <b>835.00</b> |
| <b>Z7882</b> | Locked outside only, failsecure with manual deadbolt for Privacy Feature            | <b>406.00</b> | <b>835.00</b> |



**VOLTAGE - Z7835/7870/7872/7880/7882 ONLY**

Specify voltage for Z7835/7870/7872/7880/7882 function only. Leave blank for all other functions which are 12/24VDC, field selectable

|                |                |            |
|----------------|----------------|------------|
| <b>E</b> 12VDC | <b>C</b> 24VDC | <b>N/C</b> |
|----------------|----------------|------------|

**SPECIFY HAND**

|                     |                               |                                       |            |
|---------------------|-------------------------------|---------------------------------------|------------|
| <b>L</b> Left hand  | <b>LR</b> Left hand reversed  | All hands are field reversible        | <b>N/C</b> |
| <b>R</b> Right hand | <b>RR</b> Right hand reversed | without disassembly (exception Z7835) | <b>N/C</b> |

**SPECIFY FINISH**           **Add to List**

|                                     |              |                                |              |                                     |              |
|-------------------------------------|--------------|--------------------------------|--------------|-------------------------------------|--------------|
| <b>Q</b> 626 Dull Chrome (standard) | <b>N/C</b>   | <b>G</b> 612 Dull Bronze       | <b>52.00</b> | <b>S</b> 629 Bright Stainless Steel | <b>52.00</b> |
| <b>C</b> 605 Bright Brass           | <b>52.00</b> | <b>H</b> 613 Oil Rubbed Bronze | <b>52.00</b> | <b>U</b> 630 Dull Stainless Steel   | <b>52.00</b> |
| <b>D</b> 606 Dull Brass             | <b>52.00</b> | <b>P</b> 625 Bright Chrome     | <b>52.00</b> |                                     |              |
| <b>F</b> 611 Bright Bronze          | <b>52.00</b> |                                |              |                                     |              |

| SPECIFY LEVER TRIM |                               |            |            | Add to List                       |               |
|--------------------|-------------------------------|------------|------------|-----------------------------------|---------------|
| <b>G</b>           | Galaxy with rose              | <b>N/C</b> | <b>GE</b>  | Galaxy with escutcheon            | <b>104.00</b> |
| <b>E</b>           | Eclipse with rose             | <b>N/C</b> | <b>EE</b>  | Eclipse with escutcheon           | <b>104.00</b> |
| <b>N</b>           | Nova with rose                | <b>N/C</b> | <b>NE</b>  | Nova with escutcheon              | <b>104.00</b> |
| <b>07</b>          | Schlage equal with SDC B rose | <b>N/C</b> | <b>07E</b> | Schlage equal with SDC escutcheon | <b>104.00</b> |



**OPTIONS AND ACCESSORIES** Add to List

**Optional Outputs**

|          |   |               |
|----------|---|---------------|
| <b>R</b> | Request-to-exit. Indicates inside lever operation for access control request-to-exit input, alarm shunt, remote annunciation or CCTV activation, SPDT 5 Amp @ 30VDC | <b>83.00</b>  |
| <b>D</b> | Door position status output. Indicates door open and door closed. SPDT 5 Amp @ 30VDC. (7830/7832/7850/7852/7835 only)   | <b>83.00</b>  |
| <b>S</b> | Latched & locked status output. Indicates door latched and locked and door unlocked. SPDT 5 Amp @ 30VDC. (7830/7832/7850/7852/7835 only)                            | <b>104.00</b> |
| <b>B</b> | Deadbolt Status (7870/7872/7880/7882 only), SPDT 5Amp@30VDC   | <b>83.00</b>  |

**Optional Cable and Connectors**

|              |  |              |
|--------------|--|--------------|
| <b>CC1-5</b> | 5ft. Cable and connectors for locks without optional outputs | <b>47.00</b> |
| <b>CC3-5</b> | 5ft. Cable and connectors for locks with optional outputs    | <b>63.00</b> |

**Optional Key Cylinders** 1 required for 7850/7852/7870/7872/7880/7882 2 required for 7830/7832/7835

|                 |  |              |
|-----------------|--|--------------|
| <b>CYL-6KDQ</b> | 6 pin, 1.125" keyed different, 626 Dull Chrome | <b>32.00</b> |
| <b>CYL-6KAQ</b> | 6 pin, 1.125" keyed alike, 626 Dull Chrome     | <b>32.00</b> |

**Power Transfer Hinge**  
UL listed, 4.5", five knuckle hinge. Special finish available

|                 |  |               |
|-----------------|--|---------------|
| <b>PTH-4Q</b>   | Four wire, dull chrome   | <b>156.00</b> |
| <b>PTH-10Q</b>  | Ten wire, dull chrome  | <b>202.00</b> |
| <b>PTH-2+4Q</b> | 6-wire Electric Hinge 1-pair 16 Amp inrush, 4 Amp continuous;2-pair 1 Amp @ 12/24V | <b>182.00</b> |



**PTH**  
UL 10B Listed for 3Hr  
Fire Rated Doors  
See page 88

Price List Effective February 1, 2017

**SDC SECURITY DOOR CONTROLS**  
801 Avenida Acaso • Camarillo, CA 93012  
Email: Service@sdsecurity.com • www.sdsecurity.com

